

# ZVL SLOVAKIA, a.s.

## recommends lubricants for distribution network



### Properties

- all-purpose lubricants for wide range of applications
- wide range of temperatures
- corrosion protection
- provide required lubricating environment
- water washout resistant



### Lubricants for Daily operation

#### MOBIL UNIREX N2

- lithium complex soap based grease, refined crude oil and special additives

#### Applications:

- electromotors
- conveyor belts
- provide an excellent lubricating environment
- various machine tools

NLGI Grade	2
Thickener	Lithium – complex
Appearance	Green
Dropping point under conditions ASTM D 2265, °C	230
Grease life, DIN 51821 (Fe-9), L50hrs at 140°C, hours	283
Base Oil Viscosity, ASTM D 445,cSt at 40°C	115
Temperature range °C	-30 to 155



### Automotive lubricants

#### MOBILUX EP – 2

- lithium soap based grease, refined crude oil, extreme pressure additives

#### Applications:

- bearings exposed to extreme conditions and high loads
- material transport machinery
- industrial carts

NLGI Grade	2
Thickener	Lithium
Appearance	Brown
Dropping point under conditions ASTM D 2265, °C	190
Base Oil Viscosity, ASTM D 445,cSt at 40°C	160
Temperature range °C	-20 to 130



### Agricultural lubricants

#### MOBIL UNIREX N3

- lithium complex soap based grease, refined crude oil, special water washout resistant additives

#### Applications:

- bearings for wet and dusty environments
- agricultural machinery
- bearings for conveyor ovens
- bearings for drying ovens

NLGI Grade	3
Thickener	Lithium – complex
Appearance	Green
Dropping point under conditions ASTM D 2265, °C	230
Grease life, DIN 51821 (Fe-9), L50hrs at 140°C, hours	448
Base Oil Viscosity, ASTM D 445,cSt at 40°C	115
Temperature range °C	-20 to 165



PROFESSIONAL APPROACH TO WORLD INDUSTRY

ZVL SLOVAKIA, a.s.

Na stanicu 22 • 010 09 Žilina • Slovakia

phone: +421 41 707 60 32 • fax: +421 41 707 60 24 • sales.zvl@zvl-slovakia.sk • www.zvl-slovakia.sk